

Size		Outside Diameter		Schedule												
				10	20	30	STD	40	60	XS	80	100	120	140	160	XXS
(in)	(mm)	(in)	(mm)	Wall Thickness (in)												
3	76.2	3.500'	88.9				0.216	0.216		0.300	0.300				0.438	0.600
3 1/2	88.9	4.000	101.6				0.226	0.226		0.318	0.318					
4	101.6	4.500	114.3				0.237	0.237		0.337	0.337		0.438		0.531	0.674
5	127	5.563	141.3				0.258	0.258		0.375	0.375		0.500		0.625	0.750
6	152.4	6.625	168.2				0.280	0.280		0.432	0.432		0.562		0.719	0.864
8	203.2	8.625	219		0.250	0.277	0.322	0.322	0.406	0.500	0.500	0.594	0.719	0.812	0.906	0.875
10	254	10.750	273		0.250	0.307	0.365	0.365	0.500	0.500	0.594	0.719	0.844	1.000	1.125	1.000
12	304.8	12.750	323.8		0.250	0.330	0.375	0.406	0.562	0.500	0.688	0.844	1.000	1.125	1.312	1.000
14	355.6	14.000	355.6	0.250	0.312	0.375	0.375	0.438	0.594	0.500	0.750	0.938	1.094	1.250	1.406	

165 Joseph-Robertson, Sherbrooke, Qc. CANADA J1L 2W7

OFF: 819-569-4207 FAX: 819-563-6883 info@georocfor.ca

www.georocfor.com

Size		Outside Diameter		Schedule												
				10	20	30	STD	40	60	XS	80	100	120	140	160	XXS
(in)	(mm)	(in)	(mm)													
16	406.4	16.000	406.4	0.250	0.312	0.375	0.375	0.500	0.656	0.500	0.844	1.031	1.219	1.438	1.594	
18	457.2	18.000	457.2	0.250	0.312	0.438	0.375	0.562	0.750	0.500	0.938	1.156	1.375	1.562	1.781	
20	508	20.000	508	0.250	0.375	0.500	0.375	0.594	0.812	0.500	1.031	1.280	1.500	1.750	1.968	
22	558.8	22.000	558.8	0.250	0.375	0.500	0.375		0.875	0.500	1.125	1.375	1.625	1.875	2.125	
24	609.6	24.000	609.6	0.250	0.375	0.562	0.375	0.688	0.989	0.500	1.219	1.531	1.812	2.062	2.344	
30	762	30.000	762	0.312	0.500	0.625	0.375			0.500						
32	812.8	32.000	812.8	0.312	0.500	0.625	0.375	0.688								
34	863.6	34.000	863.6	0.312	0.500	0.625	0.375	0.688								
36	914.4	36.000	914.4	0.312	0.500	0.625	0.375	0.750								

165 Joseph-Robertson, Sherbrooke, Qc. CANADA J1L 2W7

OFF: 819-569-4207 FAX: 819-563-6883 info@georocfor.ca

www.georocfor.com